# **Septone Protecta Grit**

# **ITW Polymers & Fluids**

Chemwatch: **42041** Version No: **8.1** 

Safety Data Sheet according to WHS Regulations (Hazardous Chemicals) Amendment 2020 and ADG requirements

#### Chemwatch Hazard Alert Code: 1

Issue Date: **01/11/2019**Print Date: **09/05/2022**S.GHS.AUS.EN

## SECTION 1 Identification of the substance / mixture and of the company / undertaking

### **Product Identifier**

Product name	Septone Protecta Grit	
Chemical Name	Not Applicable	
Synonyms	Manufacturer's Code IHPG500, IHPG4,; IHPG20, IHPG170	
Chemical formula	Not Applicable	
Other means of identification	Not Available	

### Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Industrial strength waterless hand cleaner.

## Details of the supplier of the safety data sheet

Registered company name	ITW Polymers & Fluids	
Address	1-9 Nina Link, Dandenong South VIC 3175 Australia	
Telephone	02 9757 8800	
Fax	Not Available	
Website	www.itwaamtech.com.au	
Email	Not Available	

## **Emergency telephone number**

Association / Organisation	Chemwatch	CHEMWATCH EMERGENCY RESPONSE
Emergency telephone numbers	1800 039 008	+61 1800 951 288
Other emergency telephone numbers	Not Available	+61 2 9186 1132

Once connected and if the message is not in your prefered language then please dial 01

### **SECTION 2 Hazards identification**

### Classification of the substance or mixture

## HAZARDOUS CHEMICAL. NON-DANGEROUS GOODS. According to the WHS Regulations and the ADG Code.

Poisons Schedule	Not Applicable	
Classification [1]	Specific Target Organ Toxicity - Single Exposure (Narcotic Effects) Category 3	
Legend:	1. Classified by Chemwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI	

# Label elements

Hazard pictogram(s)



Signal word

Warning

## Hazard statement(s)

AUH066

Repeated exposure may cause skin dryness and cracking.

H336	May cause drowsiness of	or dizzines
ทองข	May cause ulowsilless (	JI UIZZIIIES:

# Precautionary statement(s) General

P101	If medical advice is needed, have product container or label at hand.	
P102	Keep out of reach of children.	
P103	P103 Read carefully and follow all instructions.	

## Precautionary statement(s) Prevention

P271	Use only outdoors or in a well-ventilated area.	
P261	P261 Avoid breathing mist/vapours/spray.	

## Precautionary statement(s) Response

P312	Call a POISON CENTER/doctor/physician/first aider/if you feel unwell.	
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.	

# Precautionary statement(s) Storage

P405	Store locked up.	
P403+P233	Store in a well-ventilated place. Keep container tightly closed.	

# Precautionary statement(s) Disposal

P501	Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.
------	--

Not Applicable

## **SECTION 3 Composition / information on ingredients**

### **Substances**

See section below for composition of Mixtures

## **Mixtures**

CAS No	%[weight]	Name
8052-41-3.	30-60	white spirit
Not Available	10-30	ingredients determined not to be hazardous
7732-18-5	30-60	water
Legend: 1. Classified by Chemwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 4. Classification drawn from C&L * EU IOELVs available		

## **SECTION 4 First aid measures**

# **Description of first aid measures**

Eye Contact	<ul> <li>If this product comes in contact with the eyes:</li> <li>Wash out immediately with fresh running water.</li> <li>Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.</li> <li>Seek medical attention without delay; if pain persists or recurs seek medical attention.</li> <li>Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.</li> </ul>
Skin Contact	If skin contact occurs:  Immediately remove all contaminated clothing, including footwear.  Flush skin and hair with running water (and soap if available).  Seek medical attention in event of irritation.
Inhalation	<ul> <li>If fumes or combustion products are inhaled remove from contaminated area.</li> <li>Lay patient down. Keep warm and rested.</li> <li>Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.</li> <li>Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.</li> <li>Transport to hospital, or doctor.</li> </ul>
Ingestion	<ul> <li>If swallowed do NOT induce vomiting.</li> <li>If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.</li> <li>Observe the patient carefully.</li> <li>Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.</li> </ul>

- Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.
- Seek medical advice.

## Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## **SECTION 5 Firefighting measures**

## **Extinguishing media**

The product contains a substantial proportion of water, therefore there are no restrictions on the type of extinguishing media which may be used. Choice of extinguishing media should take into account surrounding areas.

Though the material is non-combustible, evaporation of water from the mixture, caused by the heat of nearby fire, may produce floating layers of combustible substances.

In such an event consider:

foam.

## Special hazards arising from the substrate or mixture

Fire Incompatibility	None known.
Advice for firefighters	
Fire Fighting	<ul> <li>Alert Fire Brigade and tell them location and nature of hazard.</li> <li>Wear breathing apparatus plus protective gloves.</li> <li>Prevent, by any means available, spillage from entering drains or water courses.</li> <li>Use water delivered as a fine spray to control fire and cool adjacent area.</li> </ul>
Fire/Explosion Hazard	<ul> <li>The material is not readily combustible under normal conditions.</li> <li>However, it will break down under fire conditions and the organic component may burn.</li> <li>Not considered to be a significant fire risk.</li> <li>Heat may cause expansion or decomposition with violent rupture of containers.</li> <li>Decomposes on heating and produces:</li> <li>carbon dioxide (CO2)</li> <li>other pyrolysis products typical of burning organic material.</li> <li>May emit poisonous fumes.</li> <li>May emit corrosive fumes.</li> </ul>

## **SECTION 6 Accidental release measures**

**HAZCHEM** 

### Personal precautions, protective equipment and emergency procedures

Not Applicable

See section 8

### **Environmental precautions**

See section 12

## Methods and material for containment and cleaning up

Minor Spills	<ul> <li>Clean up all spills immediately.</li> <li>Avoid breathing vapours and contact with skin and eyes.</li> <li>Control personal contact with the substance, by using protective equipment.</li> <li>Contain and absorb spill with sand, earth, inert material or vermiculite.</li> </ul>
Major Spills	<ul> <li>Clear area of personnel and move upwind.</li> <li>Alert Fire Brigade and tell them location and nature of hazard.</li> <li>Wear breathing apparatus plus protective gloves.</li> <li>Prevent, by any means available, spillage from entering drains or water course.</li> </ul>

Personal Protective Equipment advice is contained in Section 8 of the SDS.

## **SECTION 7 Handling and storage**

### Precautions for safe handling

Precautions for safe handling		
Safe handling	<ul> <li>Avoid all personal contact, including inhalation.</li> <li>Wear protective clothing when risk of exposure occurs.</li> <li>Use in a well-ventilated area.</li> <li>Prevent concentration in hollows and sumps.</li> </ul>	
Other information	<ul> <li>Store in original containers.</li> <li>Keep containers securely sealed.</li> <li>No smoking, naked lights or ignition sources.</li> <li>Store in a cool, dry, well-ventilated area.</li> </ul>	

### Conditions for safe storage, including any incompatibilities

Suitable container	<ul> <li>Metal can or drum</li> <li>Packaging as recommended by manufacturer.</li> <li>Check all containers are clearly labelled and free from leaks.</li> </ul>
Storage incompatibility	Avoid reaction with oxidising agents

### **SECTION 8 Exposure controls / personal protection**

### **Control parameters**

### Occupational Exposure Limits (OEL)

## INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Australia Exposure Standards	white spirit	White spirits	790 mg/m3	Not Available	Not Available	Not Available

#### **Emergency Limits**

Ingredient	TEEL-1	TEEL-2	TEEL-3
white spirit	300 mg/m3	1,800 mg/m3	29500** mg/m3

Ingredient	Original IDLH	Revised IDLH
white spirit	20,000 mg/m3	Not Available
water	Not Available	Not Available

### **Exposure controls**

# Appropriate engineering controls

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.

# Personal protection











# Eye and face protection

- Safety glasses with side shields.
- Chemical goggles.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task.

# Skin protection

See Hand protection below

### Hands/feet protection

- Wear chemical protective gloves, e.g. PVC.
- Wear safety footwear or safety gumboots, e.g. Rubber

### Body protection

# See Other protection below

# Other protection

- Overalls.
- P.V.C apron.
- Barrier cream.
- Skin cleansing cream.

### Respiratory protection

Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

- Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.
- Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

## **SECTION 9 Physical and chemical properties**

## Information on basic physical and chemical properties

Appearance	Pink paste with a gritty texture and a slight solvent odour; mixes with water.			
Physical state	Free-flowing Paste	Relative density (Water = 1)	0.93 @ 25 deg.C	
Odour	Not Available	Partition coefficient n-octanol / water	Not Available	
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Applicable	
pH (as supplied)	9.0	Decomposition temperature	Not Available	
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available	
Initial boiling point and boiling range (°C)	100	Molecular weight (g/mol)	Not Applicable	
Flash point (°C)	Not Applicable	Taste	Not Available	
Evaporation rate	As for water	Explosive properties	Not Available	
Flammability	Not Applicable	Oxidising properties	Not Available	
Upper Explosive Limit (%)	Not Applicable	Surface Tension (dyn/cm or mN/m)	Not Available	
Lower Explosive Limit (%)	Not Applicable	Volatile Component (%vol)	74	
Vapour pressure (kPa)	Not Available	Gas group	Not Available	
Solubility in water	Partly miscible	pH as a solution (Not Available%)	Not Available	
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available	

# **SECTION 10 Stability and reactivity**

Reactivity	See section 7
Chemical stability	<ul> <li>Unstable in the presence of incompatible materials.</li> <li>Product is considered stable.</li> <li>Hazardous polymerisation will not occur.</li> </ul>
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

# **SECTION 11 Toxicological information**

### Information on toxicological effects

	labelation of the control of the con
Inhaled	Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by sleepiness, reduced alertness, loss of reflexes, lack of co-ordination, and vertigo.  Inhalation of vapours or aerosols (mists, fumes), generated by the material during the course of normal handling, may be damaging to the health of the individual.  There is some evidence to suggest that the material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage.  Inhalation of high concentrations of gas/vapour causes lung irritation with coughing and nausea, central nervous depression with headache and dizziness, slowing of reflexes, fatigue and inco-ordination.
Ingestion	Ingestion may result in nausea, abdominal irritation, pain and vomiting
Skin Contact	Repeated exposure may cause skin cracking, flaking or drying following normal handling and use.  Open cuts, abraded or irritated skin should not be exposed to this material  Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects.  Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.  There is some evidence to suggest that this material can cause inflammation of the skin on contact in some persons.
Eye	There is some evidence to suggest that this material can cause eye irritation and damage in some persons.
Chronic	Prolonged or repeated skin contact may cause drying with cracking, irritation and possible dermatitis following.  Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure.

	TOXICITY	IRRITATION
Septone Protecta Grit	Not Available	Not Available

	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: >3000 mg/kg <sup>[1]</sup>	Eye (human): 470 ppm/15m
and the contact	Inhalation(Rat) LC50; >5.5 mg/l4h <sup>[1]</sup>	Eye (rabbit): 500 mg/24h moderate
white spirit	Oral (Rat) LD50; >5000 mg/kg <sup>[1]</sup>	Eye: no adverse effect observed (not irritating) <sup>[1]</sup>
		Skin: adverse effect observed (irritating) <sup>[1]</sup>
		Skin: no adverse effect observed (not irritating) <sup>[1]</sup>
,	TOXICITY	IRRITATION
water	Oral (Rat) LD50; >90000 mg/kg <sup>[2]</sup>	Not Available
Legend:	Value obtained from Europe ECHA Registered Substances - Acute toxicity 2.* Value obtained from manufacturer's SDS.     Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances	

WHITE SPIRIT	white spirit, as CAS RN 8052-41-3
WATER	No significant acute toxicological data identified in literature search.
Septone Protecta Grit & WHITE SPIRIT	For petroleum: This product contains benzene, which can cause acute myeloid leukaemia, and n-hexane, which can be metabolized to compounds which are toxic to the nervous system. This product contains toluene, and animal studies suggest high concentrations of toluene lead to hearing loss. This product contains ethyl benzene and naphthalene, from which animal testing shows evidence of tumour formation.  Cancer-causing potential: Animal testing shows inhaling petroleum causes tumours of the liver and kidney; these are however not considered to be relevant in humans.  Mutation-causing potential: Most studies involving gasoline have returned negative results regarding the potential to cause mutations, including all recent studies in living human subjects (such as in petrol service station attendants).

Acute Toxicity	×	Carcinogenicity	×
Skin Irritation/Corrosion	×	Reproductivity	×
Serious Eye Damage/Irritation	×	STOT - Single Exposure	<b>~</b>
Respiratory or Skin sensitisation	×	STOT - Repeated Exposure	×
Mutagenicity	×	Aspiration Hazard	×

**Legend:** X − Data either not available or does not fill the criteria for classification ✓ − Data available to make classification

# **SECTION 12 Ecological information**

# Toxicity

	Endpoint	Test Duration (hr)	Species	Value	Source
Septone Protecta Grit	Not Available	Not Available	Not Available	Not Available	Not Available
	Endpoint	Test Duration (hr)	Species	Value	Source
	NOEC(ECx)	720h	Crustacea	0.024mg/l	2
white spirit	LC50	96h	Fish	0.14mg/l	2
	EC50	96h	Algae or other aquatic plants	0.277mg/l	2
	Endpoint	Test Duration (hr)	Species	Value	Source
water	Not Available	Not Available	Not Available	Not Available	Not Available
Legend:	4. US EPA, Ec	•	e ECHA Registered Substances - Ecotoxicolo pata 5. ECETOC Aquatic Hazard Assessment	•	

## **DO NOT** discharge into sewer or waterways.

# Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
water	LOW	LOW

# **Bioaccumulative potential**

<del>-</del>	
Ingredient	Bioaccumulation

Ingredient	Bioaccumulation	
	No Data available for all ingredients	

### Mobility in soil

Ingredient	Mobility
	No Data available for all ingredients

### **SECTION 13 Disposal considerations**

### Waste treatment methods

Product / Packaging disposal

- ▶ Recycle wherever possible or consult manufacturer for recycling options.
- Consult State Land Waste Authority for disposal.
- Bury or incinerate residue at an approved site.
- ▶ Recycle containers if possible, or dispose of in an authorised landfill.

### **SECTION 14 Transport information**

### **Labels Required**

Marine Pollutant	NO
HAZCHEM	Not Applicable

Land transport (ADG): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

### Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
white spirit	Not Available
water	Not Available

# Transport in bulk in accordance with the ICG Code

Product name	Ship Type
white spirit	Not Available
water	Not Available

## **SECTION 15 Regulatory information**

## Safety, health and environmental regulations / legislation specific for the substance or mixture

## white spirit is found on the following regulatory lists

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals

Australian Inventory of Industrial Chemicals (AIIC)

Chemical Footprint Project - Chemicals of High Concern List International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

## water is found on the following regulatory lists

Australian Inventory of Industrial Chemicals (AIIC)

### **National Inventory Status**

National Inventory	Status
Australia - AIIC / Australia Non-Industrial Use	Yes
Canada - DSL	Yes
Canada - NDSL	No (white spirit; water)
China - IECSC	Yes
Europe - EINEC / ELINCS / NLP	Yes

National Inventory	Status			
Japan - ENCS	Yes			
Korea - KECI	Yes			
New Zealand - NZIoC	Yes			
Philippines - PICCS	Yes			
USA - TSCA	Yes			
Taiwan - TCSI	Yes			
Mexico - INSQ	Yes			
Vietnam - NCI	Yes			
Russia - FBEPH	Yes			
Legend:	Yes = All CAS declared ingredients are on the inventory  No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.			

### **SECTION 16 Other information**

Revision Date	01/11/2019
Initial Date	01/11/2009

## **SDS Version Summary**

Version	Date of Update	Sections Updated
6.1	14/05/2013	Acute Health (swallowed), Environmental, First Aid (swallowed), Storage (storage requirement), Use
8.1	01/11/2019	One-off system update. NOTE: This may or may not change the GHS classification

### Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.